

**NEW
PRODUCTS**



NEW PRODUCTS

MOOSE AGGRO WINCHES



WE SUPPORT THE SPORT®

WWW.PARTSEUROPE.EU

1.134 KG (2.500 LB) LB AGGRO UTV WINCH

- 1.134 kg (2.500 lb) capacity
- For ATVs only
- Black powder coated finish
- IP67 waterproof sealing
- Durable planetary gear train
- Load holding brake
- Available in 15,2 m of 5 mm (50' of 3/16") wire rope or 15,2 m of 5 mm (50' of 3/16") synthetic rope
- Includes handlebar mounted rocker switch, roller fairlead (for wire rope version) and hawse fairlead (for synthetic version), zinc plated hook, contactor, power cables, and mounting plate with hardware
- Tested and certified according to EN ISO 12100:2010 & EN 50498:2010

DESCRIPTION	PART #
1.134 kg with wire rope	4505-0783
1.134 kg with synthetic rope	4505-0784



4505-0783

1.588 KG (3.500 LB) AGGRO WINCH

- 1.588 kg (3.500 lb) capacity
- For ATVs and UTVs
- Black powder coated finish
- IP67 waterproof sealing
- Durable planetary gear train
- Load holding brake
- Available in 15,2 m of 5 mm (50' of 3/16") wire rope or 15,2 m of 5 mm (50' of 3/16") synthetic rope
- Includes handlebar mounted rocker switch for ATVs, dash mounted rocker switch for UTVs, roller fairlead (for wire rope version) and hawse fairlead (for synthetic version), zinc plated hook, contactor, power cables, and mounting plate with hardware
- Tested and certified according to EN ISO 12100:2010 & EN 50498:2010

DESCRIPTION	PART #
1.588 kg with wire rope	4505-0785
1.588 kg with synthetic rope	4505-0786



4505-0785

2.041 KG (4.500 LB) AGGRO UTV WINCH

- 2.041 kg (4.500 lb) capacity
- For UTVs only
- Black powder coated finish
- IP67 waterproof sealing
- Durable planetary gear train
- Load holding brake
- Available in 15,2 m of 6 mm (50' of 7/32") wire rope or 15,2 m of 6 mm (50' of 7/32") synthetic rope
- Includes dash mounted rocker switch, corded wire remote, roller fairlead (for wire rope version) and hawse fairlead (for synthetic version), zinc plated hook, contactor, power cables, and mounting plate with hardware
- Tested and certified according to EN ISO 12100:2010 & EN 50498:2010

DESCRIPTION	PART #
2.041 kg with wire rope	4505-0787
2.041 kg with synthetic rope	4505-0788



4505-0787

SPARE PARTS

DESCRIPTION	PART #
Winch Core 1.134 kg	4505-0767
Winch Core 1.588 kg	4505-0768
Winch Core 2.041 kg	4505-0769
Wire Rope 5 mm	4505-0770
Synthetic Rope 5 mm	4505-0771
Wire Rope 6 mm	4505-0772

DESCRIPTION	PART #
Synthetic Rope 6mm	4505-0773
Contactor 1.134/1.588/2.041 kg	4505-0774
Roller Fairlead 1.134/1.588 kg	4505-0779
Roller Fairlead 2.041 kg	4505-0780
Hawse Fairlead 1.134/1.588 kg	4505-0781
Hawse Fairlead 2.041 kg	4505-0782